

**RIF. COD.**

1	B000028A24	43	B000028B19
2	C750104A01	44	C790600F01
3	B000020A04	45	C790540F01
4	C750100A01	46	C790912F01
5	C790103U01	47	B000026A08
6	B000028C12	48	C790937F01
7	C750180A01	49	B000026A06
8	C790122K02	50	B000028B24
9	B000020A37	51	B000028B24
10	C565181A01	52	B000028B24
11	C750200A01	53	C790720F01
12	B000020A38	54	B000028B20
13	B000020A44	55	C565180A01
14	C790201U01	56	C565689A01
15	B000020A42	57	C790484F01
16	C750162A01	58	B000026A15
17	C790242F01	59	D790441U01
18	B000020A49	60	B000026A15
19	C770222U01	61	C790871F01
20	C790220F01	62	B000028E06
21	B000020B43	63	C275843K01
22	C790225F01	64	B000026A04
23	C790240F01	65	B000020A48
24	B000020A49	66	C465282A01
25	B000020A47	67	B000020A67
26	B000020A56	68	C790300F01
27	C790243F01	69	B000020A20
28	C790244F01	70	C430401A02
29	C790251U02	71	B000020A17
30	D790265A01	72	C790345F01
31	B000023A06	73	B000020A15
32	C790528U01	74	B000020A73
33	C790525F01	75	C790325F01
34	B000022C04	76	D790123K02
35	B000028B42	77	D790202U01
36	C790500F01	78	D790242F01
37	C710842U03	79	D790226F01
38	C790681F01	80	D790241F01
39	B000028B26	81	D790243F01
40	C790662F01	82	D465283A01
41	B000022D11	83	D790300F01
42	B000028B11	84	D790345F01

Codice A790000F01  
 Modello M90  
 Tipo Funito FENCING 4.0  
 Lungh. min. 25 mm.  
 Lungh. max. 50 mm.

Kode A790000F01  
 Modell M90  
 Klammer Typ FENCING 4.0  
 Min. Länge 25 mm.  
 Max. Länge 50 mm.

Code A790000F01  
 Model M90  
 Staple type FENCING 4.0  
 Min. length 25 mm.  
 Max. length 50 mm.

Code A790000F01  
 Modèle M90  
 Agrafe type FENCING 4.0  
 Longueur min. 25 mm.  
 Longueur max. 50 mm.

Código A790000F01  
 Modelo M90  
 Grapa tipo FENCING 4.0  
 Largueza min. 25 mm.  
 Largueza max. 50 mm.

Codigo A790000F01  
 Modelo M90  
 Tipo de agrafe FENCING 4.0  
 Largura min. 25 mm.  
 Largura max. 50 mm.

**DATI TECNICI**

Peso: 4300 gr.  
 Dimensioni: 95-360-370 mm.  
 Consumo aria: 3,50 NI/colpo  
 Pressione min.: 5,0 bar  
 Pressione max.: 8,0 bar

**TECHNISCHE DATEN**

Gewicht: 4300 gr.  
 Abmessungen: 95-360-370 mm  
 Luftverbrauch: 3,50 NI/pro Sch  
 Min.Betriebsdruck: 5,0 bar  
 Max.Betriebsdruck: 8,0 bar

**TECHNICAL FEATURES**

Weight: 4300 gr.  
 Dimensions: 95-360-370 mm.  
 Air consumption: 3,50 NI/shot  
 Min.working pressure: 5,0 bar  
 Max.working pressure: 8,0 bar

**DONNEES TECHNIQUES**

Poids: 4300 gr.  
 Dimensions: 95-360-370 mm.  
 Consommation d'air: 3,50 NI/c  
 Pression de fonction min.: 5,0  
 Pression de fonction max.: 8,0

**DATOS TECNICOS**

Peso: 4300 gr.  
 Dimensiones: 95-360-370 mm.  
 Consumo de aire: 3,50 NI/disp  
 Presion min.: 5,0 bar  
 Presion max.: 8,0 bar

**CARACTERISTICAS TECNICAS**

Peso: 4300 gr.  
 Dimensões: 95-360-370 mm.  
 Consumo de ar: 3,50 NI/disp  
 Pressão min.: 5,0 bar  
 Pressão max.: 8,0 bar

**POTENZA ACUSTICA**

DIRETTIVA CEE  
 ISO-11148-13-2017  
 prEN 12549 (1999)  
 UNI EN ISO 3744 (1997)  
 LwA= 94,7 (dB)  
 LpA 60S 1M= 93,8 (dB)

**SCHALLEISTUNG**

EWG RICHTLINIE  
 ISO-11148-13-2017  
 prEN 12549 (1999)  
 UNI EN ISO 3744 (1997)  
 LwA= 94,7 (dB)  
 LpA 60S 1M= 93,8 (dB)

**NOISE POWER**

EEC DIRECTIVE  
 ISO-11148-13-2017  
 prEN 12549 (1999)  
 UNI EN ISO 3744 (1997)  
 LwA= 94,7 (dB)  
 LpA 60S 1M= 93,8 (dB)

**PUISSANCE ACOUSTIQUE**

DIRECTIVE CEE  
 ISO-11148-13-2017  
 prEN 12549 (1999)  
 UNI EN ISO 3744 (1997)  
 LwA= 94,7 (dB)  
 LpA 60S 1M= 93,8 (dB)

**POTENCIA ACUSTICA**

NORMATIVA CEE  
 ISO-11148-13-2017  
 prEN 12549 (1999)  
 UNI EN ISO 3744 (1997)  
 LwA= 94,7 (dB)  
 LpA 60S 1M= 93,8 (dB)

**POTENCIA ACUSTICA**

DIRECTIVA CEE  
 ISO-11148-13-2017  
 prEN 12549 (1999)  
 UNI EN ISO 3744 (1997)  
 LwA= 94,7 (dB)  
 LpA 60S 1M= 93,8 (dB)

**VIBRAZIONI PRODOTTE**

DIRETTIVA CEE  
 ISO-11148-13-2017  
 ISO/FDIS 8662-11 (1999)  
 ah.w.3s= 4,2 (m/s<sup>2</sup>)

**GERAETEBEZOGENER**

VIBRATIONSWERT  
 EWG RICHTLINIE  
 ISO-11148-13-2017  
 ISO/FDIS 8662-11 (1999)  
 ah.w.3s= 4,2 (m/s<sup>2</sup>)

**TOOL RELATED VIBRATION VALUE**

EEC DIRECTIVE  
 ISO-11148-13-2017  
 ISO/FDIS 8662-11 (1999)  
 ah.w.3s= 4,2 (m/s<sup>2</sup>)

**VALEUR DES VIBRATIONS PAR LA MACHINE**

DIRECTIVE CEE  
 ISO-11148-13-2017  
 ISO/FDIS 8662-11 (1999)  
 ah.w.3s= 4,2 (m/s<sup>2</sup>)

**VIBRACION PRODUCIDA**

NORMATIVA CEE  
 ISO-11148-13-2017  
 ISO/FDIS 8662-11 (1999)  
 ah.w.3s= 4,2 (m/s<sup>2</sup>)

**NIVEL DE VIBRACAO DO PRODUTO**

DIRECTIVA CEE  
 ISO-11148-13-2017  
 ISO/FDIS 8662-11 (1999)  
 ah.w.3s= 4,2 (m/s<sup>2</sup>)

